

Automatic Air Valve

Model A10

BERMAD A10 is a high quality automatic air release valve that allows efficient release of air pockets from pressurized pipelines.

With its advanced design and automatic orifice, this valve provides excellent protection against air accumulation with improved sealing in low pressure conditions.



Typical Applications

- Irrigation Control Heads – Protection against air accumulation at filtration and fertilization stations and downstream of main control valves.
- Infield Systems – Protection against air accumulation near water meters and automatic regulators.
- Landscape Irrigation – Protection against air accumulation.


Features & Benefits

- Large diameter automatic orifice – Higher flow rates.
- Dynamic sealing – Prevents leakage under low pressure conditions (0.1 bar).
- The boss on the base can be tapped with a thread for pressure gauge connection, check point or test drain for air valve function.
- Compact, simple and reliable structure whose parts are fully corrosion, chemical and fertilizer resistant – Lower maintenance and increased life span.
- Factory approval and Quality Control – Performance and specification tested and measured with specialized test bench.

Principles of Operation

Pressurized Operation:

During pressurized operation of a pipeline, air accumulates in the upper part of the air valve chamber, causing the float to gravitate downwards. This in turn causes the automatic orifice to open, releasing the accumulated air. Once the air is discharged, the water level and float rise, causing the automatic orifice to close.



Valve Selection



- Body material: Glass-reinforced plastic
- Inlet sizes: DN20, DN25 (¾", 1")
- Connections: Threaded male BSPT
- Outle: Sideways

Operational Data

- Pressure rating: ISO PN10
- Operating pressure range: 0.1- 10 bar
- Operating temperature: Water up to 60°C

Air Flow Performance Charts

Air Release (Pressurized Operation)



Orifices Specification

Size		Automatic
DN	Inch	Ad[mm²]
20	¾"	9.6
25	1"	9.6

Dimensions & Weights

Size			Side Outlet		
DN	Inch	Connection	D (mm)	H (mm)	Weight (Kg)
20	¾"	Threaded	95	136	0.35
25	1"	Threaded	95	136	0.36

Parts List and Materials

	Description	Material
1	Base BSP/NPT	Glass Reinforced Polyamide
2	Body	Glass Reinforced Polyamide
3	Float	Polypropylene
4	Peel Seal	EPDM
5	O-Ring	EPDM